

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 June 2004 (24.06.2004)


PCT

(10) International Publication Number
WO 2004/053906 A1

- (51) International Patent Classification⁷: **H01H 13/70**
- (21) International Application Number:
PCT/EP2003/050961
- (22) International Filing Date: 8 December 2003 (08.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
02102704.0 9 December 2002 (09.12.2002) EP
- (71) Applicant (for all designated States except US): **IEE INTERNATIONAL ELECTRONICS & ENGINEERING S.A.** [LU/LU]; Zone Industrielle, 6468 Echternach (LU).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **BIECK, Werner** [DE/DE]; Auf Probert, 25, 54459 Wiltingen (DE). **CHABACH, Driss** [LU/LU]; 16, An Heirich, 9676 Noertrange (LU). **DECOSTER, Yves** [FR/BE]; 1a, rue des Marronniers, B-6760 Ethe (BE). **KIRSCH, Aloyse** [LU/LU]; 37, rue des Prés, 5316 Contern (LU).
- (74) Agents: **BEISSEL, Jean et al.**; Office Ernest T. Freylinger S.A., B.P. 48, 8001 Strassen (LU).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: FOIL-TYPE SWITCHING ELEMENT



(57) Abstract: A foil-type switching element comprises a first carrier foil and a second carrier foil arranged at a certain distance from each other by means of a spacer, said spacer comprising at least one recess defining an active area of the switching element. At least two electrodes are arranged in the active area of the switching element between said first and second carrier foils in such a way that, in response to a pressure acting on the active area of the switching element, the first and second carrier foils are pressed together against the reaction force of the elastic carrier foils and an electrical contact is established between the at least two electrodes. According to the invention at least one of said first and second carrier foils comprises a multi-layered configuration with an inner supporting foil and an outer elastic activation layer for introducing a force acting on the switching element into a central region of said active area of said switching element.



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.